

Type: _____ Qty: _____

Project: _____



HELIUM LYTE

SILENTIUM 4.5

Round Bevel Trim
Fixed & Adjustable



Round Bevel Trimless
Fixed & Adjustable



Design Features:

- Made with high powered BRIDGELUX led chip that maintains high lumens per watt with 90+ CRI.
- Available in TRIAC / 0-10v and DALI dimming.
- Standard remodel installation, new construction housing available.
- LED modules and drivers are easily replaceable.
- IC Rated Housing Available up to 35W.
- Extruded aluminium heat sink ensures optimal heat dissipation and LED life.
- Available with accessories for optics.
- 5 Year warranty.



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek

SILENTIUM 4.5

Specs Code:

FIXTURE ID 1	TRIM OPTION 3	TRIM STYLE 4	TRIM FINISH 4	LUMENS/ WATT 5
Silentium 4.5 Round SLTM4.5-RO	Trim TRM	Fixed FX	White WH	L1050 / 14W L10/14W
	Trimless TRML	Adjustable AD	Black BLK	L1215 / 18W L12/18W
				L1620 / 21W L16/21W
				L2775 / 35W L27/35W
				L3305 / 45W L33/45W
LED OPTION 6	BEAM ANGLE 7	DIMMING 8	HOUSING 9	VOLTAGE 10
2700K 27K	25 Degree 25D	TRIAC TRIAC	New Construction NC	120V 120V
3000K 30K	30 Degree 30D	0-10V DMV	IC Rated Housing IC	120-277V UNV
3500K 35K	45 Degree 45D	DALI DALI		
4000K 40K	55 Degree 55D			
Dim To Warm DTW				

Order Guide:

1	2	3	4	5	6
7	8	9	10		

*Example : SLTM4.5-RO-TRM-FX-BLK-L10/14W-40K-55D-TRIAC-NC-UNV

Accessories :



	Solite Lense [SL]	Frosted Lense [FR]	Hex Louver [HL]
OPTICS			



SILENTIUM 4.5

Product Details:

Round Bevel Trim Fixed





Ø4 1/2" (Ø115mm)

Ø5 1/2" (Ø140mm)

○ Cut out : 5 1/32" (128mm)

Round Bevel Trim Adjustable




Ø4 1/2" (Ø115mm)

Ø5 1/2" (Ø140mm)

○ Cut out : 5 1/32" (128mm)

Round Bevel Trimless Fixed





Ø4 1/2" (Ø115mm)

8 1/16" (205mm)

○ Cut out : 5 1/32" (128mm)

Round Bevel Trimless Adjustable



Ø4 1/2" (Ø115mm)

8 1/16" (205mm)

○ Cut out : 5 1/32" (128mm)



Warranty



DAMP Rated



TRIAC



Dimming



DALI





Intertek



SILENTIUM 4.5

Product Details:

New Construction Plate For Trim / Trimless



IC BOX For Up to 35W



Warranty



Damp Rated



TRIAC



Dimming







DALI



Intertek

SILENTIUM 4.5


Mounting Details:




SILENTIUM 4.5

Photometric:

Round Fixed -35W-25D



Round Adjustable -35W-30D



Lighting Chart:

WATT	LUMENS	CCT	CRI
14W	1050 lm	3000K	CRI90
18W	1215 lm	3000K	CRI90
21W	1620 lm	3000K	CRI90
35W	2775 lm	3000K	CRI90
45W	3305 lm	3000K	CRI90



Warranty



DAMP Rated



TRIAC



Dimming




DALI



Intertek

SILENTIUM 4.5

Driver Details:




22B-PUP20A-1WMC	0/1-10V
22B-PUP20D-1WMC	DALI
22B-PUP20T-1LMC	TRIAC

* Suitable for 14-21W

Internal space dimension:

L 8 1/4" (209mm) X W 1 7/8" (48mm) X H 1 5/16" (33mm)



16B-PUP40A-1WMC-850	0/1-10V
16B-PUP40D-1WMC-850	DALI
16B-PUP40T-1LMC-850	TRIAC

* Suitable for 25-30W

Internal space dimension:

L 9 13/16" (250mm) X W 2 1/2" (64mm) X H 1 5/16" (34mm)

16B-PUP40A-1WMC-1200	0/1-10V
16B-PUP40D-1WMC-1200	DALI
16B-PUP40T-1LMC-1200	TRIAC

* Suitable for 35-45W



SILENTIUM 4.5

Technical Details:

Material	Aluminium
Trim Options	Trim / Trimless
Trim Style	Fixed / Adjustable
Trim Finish	White / Black
Lumens	Upto 3305lm Non IC And 2775lm IC Rated
Wattage	14W / 18W / 21W / 35W / 45W
Efficacy	75 Lm/W
UGR	<16
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K / DTW
Beam Angle	25° / 30° / 45° / 55°
Dimming	TRIAC / 0-10V / DALI
Voltage	120V / 120-277V
Housing	Non IC Rated / IC Rated
Certification	ETL LISTED / DAMP RATED



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek