

Type:_____ Qty:_____


Project:_____




HELIUM LYTE

SILENTIUM 4.5

Square Bevel Trim
Fixed & Adjustable



Square Bevel Trimless
Fixed & Adjustable



Design Features:

- Made with high powered BRIDGELUX led chip that maintains high lumens per watt with 90+ CRI.
- Available in TRIAC / 0-10v and DALI dimming.
- Standard remodel installation, new construction housing available.
- LED modules and drivers are easily replaceable.
- IC Rated Housing Available up to 35W.
- Extruded aluminium heat sink ensures optimal heat dissipation and LED life.
- Available with accessories for optics.
- 5 Year warranty.



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek

SILENTIUM 4.5

Specs Code:

FIXTURE ID 1	TRIM OPTION 2	MOUNTING 3	TRIM STYLE 4	TRIM FINISH 5
Silentium 4.5 Square SLTM4.5-SQ	Trim TR Trimless TRL	Drywall DW	Fixed FX Adjustable AD	White WH Black BLK
LUMENS/ WATT 6	LED OPTION 7	BEAM ANGLE 8	DIMMING 9	HOUSING 10
L1050 / 14W L10/14W	2700K 27K	25 Degree 25D	TRIAC TRIAC	New Construction NC
L1215 / 18W L15/18W	3000K 30K	30 Degree 30D	0-10V DMV	IC Rated Housing IC
L1620 / 21W L16/21W	3500K 35K	45 Degree 45D	DALI DALI	Remodel RMOD
L2810 / 35W L28/35W	4000K 40K	55 Degree 55D		
L3258 / 45W L32/45W	Dim To Warm DTW			
VOLTAGE 11				
120V 120V 120-277V UNV				

Order Guide:

1	2	3	4	5	6
7	8	9	10	11	

*Example : SLTM4.5-SQ-TR-FX-WH-L10/14W-40K-55D-TRIAC-NC-UNV

Accessories :


	Solite Lense [SL]	Frosted Lense [FR]	Hex Louver [HL]
OPTICS			



SILENTIUM 4.5


Product Details:

Square Bevel Trim Fixed




 Cut out : 5 1/32" X 5 1/32" (128X128mm)

Square Bevel Trim Adjustable




 Cut out : 5 1/32" X 5 1/32" (128X128mm)

Square Bevel Trimless Fixed



 Cut out : 5 1/32" X 5 1/32" (128X128mm)

Square Bevel Trimless Adjustable





 Cut out : 5 1/32" X 5 1/32" (128X128mm)




SILENTIUM 4.5

Product Details:

New Construction Plate For Trim / Trimless



IC BOX For Upto 35W



Warranty



DAMP Rated



TRIAC



Dimming







DALI



Intertek

SILENTIUM 4.5


Mounting Details:




SILENTIUM 4.5

Photometric:

Round Fixed -35W-15D



Round Adjustable -35W-30D



Lighting Chart:

WATT	LUMENS	CCT	CRI
14W	1050 lm	3000K	CRI90
18W	1215 lm	3000K	CRI90
21W	1620 lm	3000K	CRI90
35W	2810 lm	3000K	CRI90
45W	3258 lm	3000K	CRI90



Warranty



DAMP Rated



TRIAC



Dimming




DALI



Intertek

SILENTIUM 4.5

Driver Details:



22B-PUP20A-1WMC

0/1-10V

22B-PUP20D-1WMC

DALI


22B-PUP20T-1LMC

TRIAC

* Suitable for 14-21W

Internal space dimension:

L 8 1/4" (209mm) X W 1 7/8" (48mm) X H 1 5/16" (33mm)



16B-PUP40A-1WMC-850

0/1-10V

16B-PUP40D-1WMC-850

DALI

16B-PUP40T-1LMC-850

TRIAC

* Suitable for 25-30W

Internal space dimension:

L 9 13/16" (250mm) X W 2 1/2" (64mm) X H 1 5/16" (34mm)

16B-PUP40A-1WMC-1200

0/1-10V

16B-PUP40D-1WMC-1200

DALI

16B-PUP40T-1LMC-1200

TRIAC

* Suitable for 35-45W



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek

SILENTIUM 4.5

Technical Details:

Material	Aluminium
Trim Options	Trim / Trimless
Trim Style	Fixed / Adjustable
Trim Finish	White / Black
Lumens	Upto 3258lm Non IC And 2810lm IC Rated
Wattage	14W / 18W / 21W / 35W / 45W
Efficacy	75 Lm/W
UGR	<16
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K / DTW
Beam Angle	15° / 24° / 36° / 50°
Dimming	TRIAC / 0-10V / DALI
Voltage	120V / 120-277V
Life expectancy	LM 80 > 66,000 Hrs. / LM 70 > 66,000 Hrs.
Operating Temp.	-20°C ~ 40°C (-4°F ~ 104°F)
Housing	Non IC Rated / IC Rated / Remodel
Certification	ETL LISTED / DAMP RATED



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek