

Type:_____ Qty:_____

Project:_____



HELIUM LYTE

SILENTIUM 1 WALL WASH



Round Wall Wash
Trim Fixed



Round Wall Wash
Trimless Fixed



Square Wall Wash
Trim Fixed



Square Wall Wash
Trimless Fixed

Design Features:

- Made with high powered BRIDGELUX led chip that maintains high lumens per watt with 90+ CRI.
- Available in TRIAC / 0-10v and DALI dimming.
- Standard remodel installation, new construction housing available.
- LED modules and drivers are easily replaceable.
- IC Rated Housing Available up to 10W.
- Extruded aluminium heat sink ensures optimal heat dissipation and LED life.
- 5 Year warranty.



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek

SILENTIUM 1 WALL WASH

Specs Code:

FIXTURE ID 1	TRIM OPTION 2	MOUNTING 3	TRIM STYLE 4	TRIM FINISH 5
Silentium 1 Wall Wash Round SLTM1-WW-RO	Trim TR Trimless TRL	Drywall DW	Fixed FX	White WH Black BLK
Silentium 1 Wall Wash Square SLTM1-WW-SQ				
LUMENS/ WATT 6	LED OPTION 7	BEAM ANGLE 8	DIMMING 9	HOUSING 10
L398 / 10W L39/10W	2700K 27K 3000K 30K 3500K 35K 4000K 40K Dim To Warm DTW	Wall Wash WW	TRIAC TRIAC 0-10V DMV DALI DALI	New Construction NC IC Rated Housing IC Remodel RMOD
VOLTAGE 11				
120V 120V 120-277V UNV				

Order Guide:

1	2	3	4	5	6
7	8	9	10	11	

*Example : SLTM1-WW-RO-TR-DW-FX-BLK-L39/10W-40K-WW-TRIAC-NC-UNV



Warranty



DAMP Rated



TRIAC



Dimming



DALI




Intertek


SILENTIUM 1 WALL WASH

Product Details:


Round Wall Wash Trim Fixed




Round Wall Wash Trimless Fixed



Square Wall Wash Trim Fixed



Square Wall Wash Trimless Fixed




SILENTIUM 1 WALL WASH


Product Details:

Round Wall Wash

New Construction Plate for Trim / Trimless




IC Box For Upto 10W




Square Wall Wash

New Construction Plate for Trim / Trimless



IC Box For Upto 10W



Warranty



DAMP Rated



TRIAC



Dimming







DALI



Intertek

SILENTIUM 1 WALL WASH


Mounting Details:



SILENTIUM 1 WALL WASH


Photometric:

Round Adjustable -10W-Wall Wash



h (m)	D (m)	E (lx)
Wallwash		
1.0	0.48	861
2.0	0.96	215
3.0	1.45	95
4.0	1.93	53
5.0	2.41	34

Square Adjustable -10W-Wall Wash



h (m)	D (m)	E (lx)
Wallwash		
1.0	0.48	861
2.0	0.96	215
3.0	1.45	95
4.0	1.93	53
5.0	2.41	34

Lighting Chart:

WATT	LUMENS	CCT	CRI
10W	398 lm	3000K	CRI90



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek



SILENTIUM 1 WALL WASH

Remote Driver Details:


PWM 5 in 1 Dimmable LED driver



HL-040-DW

Triac / 0-10V/1-10V/Potentiometer/10V
Multi-current output series 40W
For 1~3T


Gear Box




HL-040-DWJ

Triac/Phase, 0-10V, 1-10V, Potentiometer
10V PWM 5 in 1 dimming
40W 1~3T

Installation For Non-IC



Installation For IC Box



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek

SILENTIUM 1 WALL WASH

Technical Details:

Material	Aluminium
Trim Options	Trim / Trimless
Trim Style	Fixed
Trim Finish	White / Black
Lumens	Upto 398lm Non IC And IC Rated
Wattage	10W
Efficacy	39 Lm/W
UGR	<16
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K / DTW
Beam Angle	Wall Wash
Dimming	TRIAC / 0-10V / DALI
Voltage	120V / 120-277V
Life expectancy	LM 80 > 66,000 Hrs. / LM 70 > 66,000 Hrs.
Operating Temp.	-20°C ~ 40°C (-4°F ~ 104°F)
Housing	Non IC Rated / IC Rated / Remodel
Certification	ETL LISTED / DAMP RATED



Warranty



DAMP Rated



TRIAC



Dimming



DALI



Intertek