


Type:\_\_\_\_\_ Qty:\_\_\_\_\_

Project:\_\_\_\_\_




HELIUM LYTE

# INSPIRA 2



Square Trim



Square Trimless

## Design Features:

- Inspira 2D fixed 2" Downlight offers specification-grade performance and features, in a completely modular & field-configurable system. Every light engine integrates with any of the trims, and every trim works with all of the ceiling application and housing options.
- Made with high powered BRIDGELUX led chip that maintains high lumens per watt with 90 +CRI / Fixture comes with both Single CCT and Dim To Warm options.
- Available in both TRIAC and 0-10V dimming.
- Standard remodel installation, new construction housing available.
- LED modules and drivers are easily replaceable.
- Extruded aluminium heat sink ensures optimal heat dissipation and LED life.
- 5 Year warranty.



Warranty



Damp Rated



TRIAC



Dimming



Intertek

# INSPIRA 2

## Specs Code:

FIXTURE ID <span>1</span>	TRIM OPTION <span>2</span>	TRIM FINISH <span>3</span>	LUMENS/ WATT <span>4</span>	LED OPTION <span>5</span>
Inspira 2 Square <b>INS2SQ</b>	Trim <b>TRM</b>	White <b>WH</b>	L700 / 09W <b>L70/09W</b>	2700K <b>27K</b>
	Trimless <b>TRML</b>	Black <b>BLK</b>	L1200 / 14W <b>L12/14W</b>	3000K <b>30K</b>
		Custom <b>CSTM</b>	L1700 / 24W <b>L17/24W</b>	3500K <b>35K</b>
				4000K <b>40K</b>
				5000K <b>50K</b>
				Dim To Warm <b>DTW</b>
BEAM ANGLE <span>6</span>	DIMMING <span>7</span>	HOUSING* <span>8</span>	VOLTAGE <span>9</span>	
15 Degree <b>15D</b>	TRIAC <b>TRIAC</b>	New Construction <b>NC</b>	120V <b>120V</b>	
24 Degree <b>24D</b>	0-10V <b>DMV</b>	Remodel <b>RMOD</b>	120-277V <b>UNV</b>	
36 Degree <b>36D</b>				
60 Degree <b>60D</b>				

\*Inspira is not available with an IC box configuration.

## Order Guide:

<span>1</span>	<span>2</span>	<span>3</span>	<span>4</span>	<span>5</span>	<span>6</span>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<span>7</span>	<span>8</span>	<span>9</span>			
<input type="text"/>	<input type="text"/>	<input type="text"/>			



\*Example : INS2SQ-TRM-BLK-L70/09W-40K-60D-TRIAC-NC-UNV




# INSPIRA 2



## Product Details:


Square Bevel Trim Fixed - 9W



 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

Square Bevel Trimless Fixed - 9W



 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

\*All Dimensions are millimeters (Inches) unless otherwise indicated.



Warranty



Damp Rated



TRIAC



Dimming






Intertek

# INSPIRA 2



## Product Details:


Square Bevel Trim Fixed - 14W



 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

Square Bevel Trimless Fixed - 14W



 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

\*All Dimensions are millimeters (Inches) unless otherwise indicated.



Warranty



Damp Rated



TRIAC



Dimming




Intertek




# INSPIRA 2


## Product Details:


Square Bevel Trim Fixed - 24W



Square Bevel Trimless Fixed - 24W



 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

 CUT-OUT : [2 3/4"] Ø68mm X [2 3/4"] Ø68mm

\*All Dimensions are millimeters (Inches) unless otherwise indicated.

  
5  
Year  
Warranty

  
IP44  
Damp Rated

  
TRIAC

  
0-10V  
Dimming



  
ETL  
Intertek

# INSPIRA 2

## Product Details:

New construction housing plate for Square Downlight



Part number - 503047





# INSPIRA 2

## Photometric:

### Square Fixed -09W-36D



### Square Fixed -14W-36D



## Lighting Chart:

WATT	LUMENS	CCT	CRI
09W	700 lm	3000K	CRI90
14W	1200 lm	3000K	CRI90
24W	1700 lm	3000K	CRI90



# INSPIRA 2

## Technical Details:

Material	Aluminium
Trim Options	Trim / Trimless
Trim Style	Fixed
Trim Finish	White / Black
Lumens	Upto 1700lm
Wattage	09W / 14W / 24W
Efficacy	80 Lm/W
UGR	<19
CRI	90+
CCT	2700K / 3000K / 3500K / 4000K / 5000K
	/ Dim To Warm (DTW)
Beam Angle	15° / 24° / 36° / 60°
Dimming	TRIAC / 0-10V
Voltage	120V / 120-277V
Operating Temp.	-20°C ~ 40°C (-4°F ~ 104°F)
Housing	Non IC Rated / Remodel
Certification	ETL LISTED / DAMP RATED



Warranty



Damp Rated



TRIAC



Dimming



Intertek