
Helium Lyte











Silentium

Transform your space into a well-lit haven today.






Table of CONTENT

	10
	Silentium 2"
03	16
Overview	Silentium 3"
	Olloridanio
	-
05	19
D. C. S. ANNEX S. MAY AN	
ight Distributions	Silentium 3.5"
	-
00	0.4
80	24
Silentium 1"	Silentium 4.5"



Overview

Designed base on the concept of "Light Engine Modularization", making Silentium series possible to be more exible, more practical and expandable


The features are as follows

- Modularized design-easy maintenance & replacement.
- Maximize common components to reduce stock cost.
- Speed up the progress of new series development in the future.
- Interchangeable design to increase product exibility.
- Set up design norms by modularization, minimize possible faults.

Shape

Multi Aperture

3.5




Beam Angles

Square



Light distributions



Bezel Finish



Baffle Finish



Mountings



CRI / Colour Temperatures

90+	2700k 3000k 3500k	4000k 5000k DTW 3000k-
		1800k

Dimming







Light distributions

Three light patterns to meet all the essential functions of your lighting concept Vertical lighting is provided by downlights with different beam angles; wall-wash and floor-mounted optics provide a wide range of wall and floor lighting; adjustable spotlight settings. If the functional area changes, the optics in the luminaire housing can be easily replaced without tools.



Low UGR

Optics

Deep baffle design helps reduce glare, equipped with special selected lens, the light is evenly spread towards the centre to achieve the beam angles needed, making Silentium a unique series.



Fixed 36° 36° / A 36 degrees cut-off angle brings more comfort to human eyes. Adjustable 41° A 41 degrees cut-off angle brings more comfort to human eyes. Gimbal \$ 22° 22° / A 22 degrees cut-off angle brings more comfort to human eyes.










Round / Gimbal

Square / Gimbal











Wattage

10 W

642-1207 Lumens

Trim Options

Trim/Trimless

CRI/CCT


90+ / 2700k 3000k 3500k 4000k Dim To Warm


Certifications





Bezel Finish






Baffle Finish



Black



White

Beam Angle












Shape











Dimming










SILENTIUM 1 INCH



SILENTIUM 1 INCH















7-12W

441-913 Lumens

Trim Options

Trim/Trimless

CRI/CCT

90+ / 2700k 3000k 3500k 4000k Dim To Warm

Certifications





Bezel Finish



Black



White

Baffle Finish



Black



White

Beam Angle







Shape





Round

Square

Dimming









SILENTIUM 2 INCH






2"/3"/3.5"/4"











13-20 W

1216-1825 Lumens

Trim Options

Trim/Trimless

CRI/CCT

90+ / 2700k 3000k 3500k 4000k Dim To Warm

Certifications





Bezel Finish



Black



White

Baffle Finish



Black



White

Beam Angle









Shape





Round

Square

Dimming











18-20 W

850-853 Lumens

Trim Options

Trim/Trimless

CRI/CCT

90+ / 2700k 3000k 3500k 4000k Dim To Warm

Certifications





Bezel Finish



Black



White

Baffle Finish



Black



White

Beam Angle



Wall Wash

Shape






Round

Square


Dimming














SILENTIUM 3 INCH (WALL WASH)















14-30 W

686-1497 Lumens

Trim Options

Trim/Trimless

CRI/CCT

90+ / 2700k 3000k 3500k 4000k Dim To Warm

Certifications





Bezel Finish



Black



White

Baffle Finish



Black



White

Beam Angle



Wall Wash

Shape



Round



Square



Multi

Dimming












SILENTIUM 3.5 INCH (WALL WASH)











14-45W

728-1961 Lumens

Trim Options

Trim/Trimless

CRI/CCT

90+ / 2700k 3000k 3500k 4000k Dim To Warm

Certifications





Bezel Finish



White

Baffle Finish



Black



White

Beam Angle



Wall Wash

Shape







Round

Square

Dimming














SILENTIUM 4.5 INCH (WALL WASH)

